



Bearing No. NJ226EM

r	3
D	230 mm
C	40 mm
S	1,5 mm
B	40 mm
d	130 mm
Fw	153,5 mm
B_	40
rb	2.5
r1	3
D_	230
C0	455
da	143
Z_	17
ra	2.5
DE_	209.5
DA_	28
DI_	153.5
Noun	Bearing
KBRG	4155
mass	7.31
SBRG	2
SDM_	181.5
Bore	5.118 Inch 130 Millimeter
yobi	NJ226EM
Width	1.575 Inch 40 Millimeter
LangID	1
Db max	217 mm
db min	143 mm

db max	150
dd min	168
UNSPSC	31171547
C_conv	365000
ALPHA_	0
dc min	158
Weight	8,03 Kg
r min.	3 mm
Oil rpm	3200
hidYobi	NJ226EM
GRS rpm	2600
TSR rpm	3400
r1 min.	3 mm
da min.	143 mm
rb max.	2,5 mm
Da max.	217 mm
Profile	Complete with Outer and Inner Ring
ra max.	2,5 mm
D_a max	217
db max.	150 mm
Retainer	Yes
Category	Cylindrical Roller Bearing
hidTable	ecat_NSCLDR
Snap Ring	No
Separable	Inner Ring - One Side
Macha rpm	5000
Size (mm)	130x230x40
Inventory	0.0
Prod_Type3	CRB_SR_NJ
Width (mm)	40
Weight / LBS	6.4

Bore Profile	Straight
Cage Material	Brass
Product Group	B04144
Inch - Metric	Metric
Bearing number	NJ226EM
Other Features	Standard Capacity 1 Rib Inner Ring 2 Rib Outer Ring Light Series Cage on Outer Ring ID
Relubricatable	Yes
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1 ISO P0
Long Description	130MM Bore; Straight Bore Profile; 230MM Outside Diameter; 40MM Width; Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C0-Medium Inter
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	9.055 Inch 230 Millimeter
Weight / Kilogram	0
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	130
Outer Diameter (mm)	230
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.50.00.00
Manufacturer Item Number	NJ226M
Number of Rows of	Single Row

Rollers	
(Grease) Lubrication Speed	2600 r/min
Basic static load rating (C0)	455 kN
Basic dynamic load rating (C)	365 kN