



Bearing No. 6226ZZ

D	230 mm
d	130 mm
B	40 mm
C	40 mm
r	3
Z_	10
B_	40
D_	230
ra	2.5
C0	146
fo	14.5
DI_	148.25
SRI	16.43
D_a	217
DE_	211.75
DA_	31.75
SRE	16.43
SRIN	-0.065
SBRG	2
yobi	6226ZZ
SDM_	180
SREX	0.065
KBRG	6141
bomp	0
mass	5.96
Bore	5.118 Inch 130 Millimeter
SRIX	0.065
SREN	-0.065
Noun	Bearing

ALPHA_	0
da min	143
LangID	1
r min.	3 mm
UNSPSC	31171504
da max	157 mm
C_conv	167000
Weight	5,96 Kg
ra max.	2,5 mm
hidYobi	6226ZZ
GRS rpm	2400
Da max.	217 mm
da min.	143 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	130x230x40
Enclosure	2 Metal Shields
Inventory	0.0
Width (mm)	40
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	13.1418
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6226ZZ
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.575 Inch 40 Millimeter

Long Description	130MM Bore; 230MM Outside Diameter; 40MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	9.055 Inch 230 Millimeter
Weight / Kilogram	6.25
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	130
Outer Diameter (mm)	230
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	2 400 r/min
Basic static load rating (C0)	146 kN
Basic dynamic load rating (C)	167 kN
Maximum Capacity / Filling Slot	No