



Bearing No. 497/492A

| | |
|---------------------------------|----------------------|
| R | 3,6 mm |
| d | 85,725 mm |
| D | 133,35 mm |
| T | 30,162 mm |
| B | 29,769 mm |
| C | 22,225 mm |
| r | 3,3 mm |
| Da | 128 mm |
| Ab | 2,1 mm |
| Aa | 2,5 mm |
| Db | 120 mm |
| da | 93 mm |
| db | 99 mm |
| a - | 0,8 mm |
| Weight | 1,4 Kg |
| Size (mm) | 85.725x133.35x30.162 |
| Width (mm) | 30,162 |
| Factor (K) | 1,31 |
| Factor (G1) | 104,6 |
| Factor (Cg) | 0,0352 |
| Factor (G2) | 29,3 |
| Bearing number | 497/492A |
| Bore Diameter (mm) | 85,725 |
| Outer Diameter (mm) | 133,35 |
| Calculation factor (e) | 0,44 |
| Basic static load rating (C0) | 216 kN |
| Basic dynamic load rating (C1) | 143 kN |
| Basic dynamic load rating (C90) | 37,1 |

| | |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 28,2 |
|----------------------------------|------|