



Bearing No. NJ2308-E-TVP2

|                    |  |
|--------------------|--|
| s                  | 2,7 mm / Axial displacement facility from central position |
| d                  | 40 mm  |
| D                  | 90 mm  |
| B                  | 33 mm  |
| m                  | 0,978 kg / Weight  |
| F                  | 52 mm  |
| Size (mm)          | 40x90x33   |
| Width (mm)         | 33   |
| $n_B$              | 6000 1/min / Reference speed                               |
| $n_G$              | 9500 1/min / Limiting speed                                |
| $D_1$              | 75,9 mm  |
| $d_1$              | 57,6 mm  |
| $C_r$              | 132000 N / Dynamic load rating (radial)                    |
| Bearing number     | NJ2308-E-TVP2  |
| $C_{Or}$           | 119000 N / Static load rating (radial)                     |
| $C_{Ur}$           | 21600 N  |
| $r_{min}$          | 1,5 mm   |
| $r_{a max}$        | 1,5 mm   |
| $r_1 min$          | 1,5 mm   |
| $d_{c min}$        | 60 mm  |
| $d_{a max}$        | 51 mm  |
| $D_{a max}$        | 81 mm  |
| $d_{a min}$        | 49 mm  |
| Bore Diameter (mm) | 40   |

|                     |    |
|---------------------|----|
| Outer Diameter (mm) | 90 |
|---------------------|----|