



Bearing No. NJ2310-E-TVP2 + HJ2310-E

| | |
|----------------|--|
| m | 1,77 kg / Weight |
| F | 65 mm |
| E | 97 mm |
| d | 50 mm |
| D | 110 mm |
| B | 40 mm |
| s | 4,2 mm / Axial displacement facility from central position |
| Size (mm) | 50x110x40 |
| Width (mm) | 40 |
| C_r | 193000 N / Dynamic load rating (radial) |
| m_1 | 0,156 kg |
| B_2 | 14,5 mm |
| d_1 | 71,3 mm |
| D_1 | 92,5 mm |
| B_1 | 8 mm |
| n_G | 7800 1/min / Limiting speed |
| n_B | 5000 1/min / Reference speed |
| C_{0r} | 187000 N / Static load rating (radial) |
| Bearing number | NJ2310-E-TVP2 + HJ2310-E |
| C_{ur} | 34500 N / Fatigue limit load, radial |
| r_{min} | 2 mm |
| $r_{a\ max}$ | 2 mm |
| $r_{1\ min}$ | 2 mm |

| | |
|--|---|
| $d_{a \min}$ | 61 mm |
| $d_{a \max}$ | 63 mm |
| $D_{a \max}$ | 99 mm |
| $d_{c \min}$ | 73 mm |
| Bore Diameter (mm) | 50 |
| Outer Diameter (mm) | 110 |
| - HJ2310-E / Designation, L-section ring | HJ2310E / Designation, Lsection ring |