



Bearing No. 7300DT

D	35 mm
a	1.0 mm
C	11 mm
B	11 mm
d	10 mm
r1	0.3 mm
2B	22 mm
Width	11 mm
r min.	0.6 mm
Weight	0.055 Kg
ra max.	0.3 mm
r1 min.	0.3 mm
da min.	12 mm
Da max.	32.4 mm
ra (max)	0.6 mm
da1 (min)	15 mm
Bore Size	10 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.3 mm
Size (mm)	10x35x11
da2 (min)	12 mm
Da2 (max)	32.4 mm
Da1 (max)	30 mm
Width (mm)	11
Configuration	Duplex
Bearing number	7300DT
Angle (?)	30 °
Outside Diameter	35 mm
Static Load Rating	8,600 N

Bore Diameter (mm)	10
Dynamic Load Rating	15,100 N
Outer Diameter (mm)	35
Limiting Speed - Oil	21,000 rpm
Fillet Radius/Chamfer	0.6 mm
Limiting Speed - Grease	16,000 rpm
(Grease) Lubrication Speed	16000 r/min
Basic dynamic load rating (C)	15,1 kN
Basic static load rating (C0)	8,6 kN