



Bearing No. NJ2313-E-TVP2

|                    |  |
|--------------------|--|
| S                  | 4 mm / Axial displacement facility from central position |
| d                  | 65 mm  |
| D                  | 140 mm   |
| B                  | 48 mm  |
| m                  | 3,38 kg / Weight   |
| F                  | 82,5 mm  |
| Size (mm)          | 65x140x48  |
| Width (mm)         | 48   |
| $n_B$              | 4050 1/min / Reference speed                             |
| $n_G$              | 5900 1/min / Limiting speed                              |
| $D_1$              | 118,6 mm   |
| $d_1$              | 90,5 mm  |
| $C_r$              | 295000 N / Dynamic load rating (radial)                  |
| Bearing number     | NJ2313-E-TVP2  |
| $C_{Or}$           | 285000 N / Static load rating (radial)                   |
| $C_{Ur}$           | 53000 N  |
| $r_{min}$          | 2,1 mm   |
| $r_{a\ max}$       | 2,1 mm   |
| $r_1\ min$         | 2,1 mm   |
| $d_{c\ min}$       | 93 mm  |
| $d_{a\ max}$       | 81 mm  |
| $D_{a\ max}$       | 128 mm   |
| $d_{a\ min}$       | 77 mm  |
| Bore Diameter (mm) | 65   |

|                     |     |
|---------------------|-----|
| Outer Diameter (mm) | 140 |
|---------------------|-----|