



Bearing No. 6234

D	310 mm
d	170 mm
B	52 mm
C	52 mm
r	4
Z_	12
B_	52
ra	3
C0	224
fo	15.3
D_	310
D_a	294
DE_	274.925
DA_	34.925
SRI	18.07
DI_	205.075
SRE	18.07
SREN	-0.065
Bore	6.693 Inch 170 Millimeter
mass	15.8
SBRG	2
Noun	Bearing
SRIX	0.065
KBRG	6101
SRIN	-0.065
SREX	0.065
SDM_	240
bomp	0
yobi	6234

LangID	1
da min	186
UNSPSC	31171504
Weight	15,8 Kg
C_conv	212000
ALPHA_	0
da max	215
r min.	4 mm
da min.	194 mm
Oil rpm	2200
Da max.	288 mm
ra max.	3 mm
GRS rpm	1800
hidYobi	6234
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Size (mm)	170x310x52
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	52
Prod_Type3	DGBB_SR_OT
Weight / LBS	34.839
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6234
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	170MM Bore; 310MM Outside Diameter;

	52MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	12.205 Inch 310 Millimeter
Outer Race Width	2.047 Inch 52 Millimeter
Weight / Kilogram	16
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	170
Outer Diameter (mm)	310
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
Basic static load rating (C0)	224 kN
Basic dynamic load rating (C)	212 kN
Maximum Capacity / Filling Slot	No