



Bearing No. CEX210

|            |            |
|------------|------------|
| N          | 2,7 mm     |
| e          | 1,5 mm     |
| r          | 1.5        |
| G          | M8x1       |
| b          | 2.7 mm     |
| J          | 3,7 mm     |
| s          | 24,6 mm    |
| m          | 6,5 mm     |
| a          | 4 mm       |
| S          | 24.6 mm    |
| C          | 24 mm      |
| B          | 62,7 mm    |
| D          | 90 mm      |
| d          | 50 mm      |
| B1         | 49,2 mm    |
| d1         | 69.5 mm    |
| C1         | 5.6 mm     |
| B2         | 18.3 mm    |
| C0         | 23.2 kN    |
| J2         | 18,3 mm    |
| N1         | 86,79 mm   |
| SW         | 4 mm       |
| D2         | 69,5 mm    |
| H1         | 5,6 mm     |
| Weight     | 1,01 Kg    |
| T min.     | -20 °C     |
| T max.     | 100 °C     |
| Size (mm)  | 50x90x62.7 |
| Thread (G) | M8x1       |
| Width (mm) | 62,7       |

|   |         |
|---|---------|
| Bearing number                              | CEX210  |
| Bore Diameter (mm)                          | 50      |
| Outer Diameter (mm)                         | 90      |
| Basic dynamic load rating (C)               | 35,1 kN |
| Recommended tightening torque for set screw | 11.5 Nm |