



Bearing No. CRB25/72

	CR52/72 / Designation of rubber interliner
m	0,32 kg / Weight
d	25 mm
D	73 mm
C	25 mm
Bore	0.984 Inch 25 Millimeter
Category	Insert Bearings Cylindrical OD
Inventory	0.0
Size (mm)	25x73x36
Snap Ring	No
Seal Type	Double Lip Contact
Width (mm)	36
C _r	14900 N / Dynamic load rating (radial)
C _g	1000 N / Rubber ring: load carrying capacity
D ₂	46 mm
Product Group	B00308
S ₂	12,5 mm
Inch - Metric	Metric
D ₁	80 mm
C ₁	5 mm
B ₁	31 mm
B ₂	36 mm
Relubricatable	No
Bearing number	CRB25/72
Other Features	Single Row With Inter Liner Metric

C_{Or}	7800 N / Static load rating (radial)
Rolling Element	Ball Bearing
Mounting Method	Eccentric Collar
Long Description	25MM Bore; Narrow Inner Ring; 15MM Outer Race Width; 73MM Outside Diameter; Eccentric Collar; Ball Bearing; 31MM Length Thru Bore; Not Relubricatable; Double Lip Contact Seal; No Snap Ring
Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.874 Inch 73 Millimeter
Length Thru Bore	1.22 Inch 31 Millimeter
Weight / Kilogram	0.299
Manufacturer Name	SCHAEFFLER GROUP
$d_{3 \max}$	37,5 mm
Outer Race Profile	Cylindrical
Inner Race Profile	Narrow Inner Ring
Bore Diameter (mm)	25
Outer Diameter (mm)	73
Minimum Buy Quantity	N/A
- RAE25-NPP / Designation bearing	RAE25NPP / Designation bearing
- / Temperature -20 °C to +85 °C	/ Temperature 20 °C to +85 °C