



### Bearing No. CRB35/110

	CR72/110 / Designation of rubber interliner
d	35 mm
D	112,3 mm
m	0,56 kg / Weight
C	30 mm
Bore	1.378 Inch   35 Millimeter
Category	Insert Bearings Cylindrical OD
Snap Ring	No
Size (mm)	35x112.3x44.4
Seal Type	Double Lip Contact
Inventory	0.0
Width (mm)	44,4
D <sub>1</sub>	120 mm
Product Group	B00308
C <sub>1</sub>	5 mm
S <sub>2</sub>	15 mm
B <sub>1</sub>	39 mm
B <sub>2</sub>	44,4 mm
C <sub>g</sub>	1500 N / Rubber ring: load carrying capacity
C <sub>r</sub>	27500 N / Dynamic load rating (radial)
Inch - Metric	Metric
D <sub>2</sub>	64 mm
Relubricatable	No
Other Features	Single Row   With Set Screw   With Inter Liner   Corrotect Coating

	Metric
Bearing number	CRB35/110
$C_{Or}$	15300 N / Static load rating (radial)
Rolling Element	Ball Bearing
Mounting Method	Eccentric Collar
Outside Diameter	4.421 Inch   112.3 Millimeter
Long Description	35MM Bore; Narrow Inner Ring; 19MM Outer Race Width; 112.3MM Outside Diameter; Eccentric Collar; Ball Bearing; 38.9MM Length Thru Bore; Not Relubricatable; Double Lip Contact Seal; No Snap Ring
Length Thru Bore	1.531 Inch   38.9 Millimeter
Outer Race Width	0.748 Inch   19 Millimeter
Manufacturer Name	SCHAEFFLER GROUP
Weight / Kilogram	0.635
$d_{3 \max}$	51 mm
Inner Race Profile	Narrow Inner Ring
Outer Race Profile	Cylindrical
Bore Diameter (mm)	35
Outer Diameter (mm)	112,3
Minimum Buy Quantity	N/A
- RAE35-NPP / Designation bearing	RAE35NPP / Designation bearing
- / Temperature -20 °C to +85 °C	/ Temperature 20 °C to +85 °C