



Bearing No. BMD-6206/064S2/UA108A

L	565 mm
d	30 mm
D	62 mm
B	16 mm
b	1.9 mm
C	3.28 mm
Category	Bearings
Inventory	0.0
Size (mm)	62x30x22.2
Width (mm)	22,2
D ₃	59.61 mm
r ₀	0.6 mm
Product Group	B00308
D ₂	58.1 mm
D ₁	54.1 mm
d ₂	37.4 mm
B ₁	22.2 mm
d ₁	40.36 mm
Limiting speed	7500 r/min
Bearing number	BMD-6206/064S2/UA10 8A
Period accuracy	± 4 %
Mass sensor unit	0.242 kg
Weight / US pound	0.01
Manufacturer Name	SKF
Bore Diameter (mm)	62
Outer Diameter (mm)	30
d _a - min.	35 mm
Minimum Buy Quantity	N/A

d_b - min.	35 mm
r_a - max.	1 mm
Cable connector type	AMP Superseal
D_a - max.	57 mm
d_b - max.	40 mm
$r_{1,2}$ - min.	1 mm
Phase shift output signal	90 °
Basic dynamic load rating - C	19.5 kN
Tolerance cable length L - ±	10 mm
Fatigue load limit - P_u	0.475 kN
Calculation factor - k_r	0.025
Calculation factor - f_0	14
Tolerance phase shift output signal	± 30 °
Number of pulses per revolution - N	64
Basic static load rating - C_0	11.2 kN