



Bearing No. 4T-30311D

B	29 mm
e	0.83
d	55 mm
D	120 mm
T	31,5 mm
C	21 mm
a	38 mm
Y2	0.73
Sa	4 mm
d1	88.5 mm
Y0	0.4
Sb	10,5 mm
Mass	1.59 kg
ra max	2 mm
Weight	1,59 Kg
Ca min	4 mm
Db min	113 mm
r min.	2,5 mm
Da max	110 mm
rs min	2.5 mm
Da min	94 mm
Cb min	10.5 mm
db min	67 mm
da max	68 mm
r1s min	2 mm
ra max.	2 mm
r1a max	2 mm
Db min.	113 mm
db max.	68 mm
Da max.	110 mm

da min.	67 mm
r1 min.	2 mm
ra1 max.	2 mm
Category	Roller Bearings
Size (mm)	55x120x31.5
Inventory	0.0
Nlim (oil)	3,800 rpm
Width (mm)	31,5
Nlim (grease)	2,900 rpm
Product Group	B04336
Bearing number	4T-30311D
Static load, C0	154 kN
Dynamic load, C	132 kN
ISO 355 reference	T7FB055
Weight / Kilogram	0
Manufacturer Name	NTN
Bore Diameter (mm)	55
Outer Diameter (mm)	120
Minimum Buy Quantity	N/A
Calculation factor (e)	0,83
Fatigue limit load, Cu	18.8 kN
(Oil) Lubrication Speed	3 800 r/min
Calculation factor (Y0)	0,4
(Grease) Lubrication Speed	2 900 r/min
Rating life coefficient, A2	1.4
Basic static load rating (C0)	154 kN
Basic dynamic load rating (C)	132 kN
Max operating temperature, Tmax	120 °C
Min operating temperature, Tmin	-40 °C

Characteristic cage frequency, FTF	0.42 Hz
Characteristic inner ring frequency, BPF1	9.24 Hz
Characteristic outer ring frequency, BPF0	6.76 Hz
Characteristic rolling element frequency, BSF	5.52 Hz