



Bearing No. T7FC060

| | |
|------|---------|
| D | 125 mm |
| d | 60 mm |
| T | 37 mm |
| B | 33,5 mm |
| C | 26 mm |
| a | 41,3 mm |
| e | 0.82 |
| Cr | 15400 |
| Y0 | 0.4 |
| db | 72 |
| da | 78 |
| Y1 | 0.73 |
| B_ | 33.5 |
| Sb | 11 |
| C0 | 197 |
| Sa | 4 |
| D_ | 125 |
| Z_ | 18 |
| C_ | 26 |
| C0r | 20100 |
| DA_ | 14.197 |
| Iso | 7FC |
| DE_ | 104.054 |
| D_b | 119 |
| DI_ | 78.117 |
| SBRG | 7FC |
| SDM_ | 91.086 |
| D_a2 | 94 |
| KBRG | 3111 |
| yobi | T7FC060 |

| | |
|----------|-------------|
| D_a1 | 111 |
| mass | 2.03 |
| TC-RA | 120.698 |
| r min. | 3 mm |
| Weight | 2,03 Kg |
| TC-DA1 | 15.784 |
| TC-DA2 | 12.61 |
| TC-SLR | 24.5 |
| Da min | 94 mm |
| LangID | 1 |
| ALPHA_ | 28.65 |
| Db min. | 119 mm |
| Oil rpm | 3800 |
| db max. | 72 mm |
| Da max. | 111 mm |
| ra max. | 2,5 mm |
| hidYobi | T7FC060 |
| da min. | 78 mm |
| T-ALP21 | 57 |
| rb max. | 2,5 mm |
| T-ALP22 | 18 |
| T-ALP23 | 0 |
| GRS rpm | 2800 |
| inner r | 3 |
| outer r | 3 |
| r1 min. | 3 mm |
| hidTable | ecat_NSTPRM |
| TC-BET23 | 0 |
| TC-BET21 | 7 |
| inner ra | 2.5 |
| outer rb | 2.5 |
| TC-BET22 | 30 |
| | |

| | |
|-------------------------------|------------|
| Size (mm) | 60x125x37 |
| Width (mm) | 37 |
| Prod_Type3 | TRBSR_MD_A |
| Bearing number | T7FC060 |
| Bore Diameter (mm) | 60 |
| Outer Diameter (mm) | 125 |
| Calculation factor (e) | 0,82 |
| Calculation factor (Y0) | 0,4 |
| (Oil) Lubrication Speed | 3800 r/min |
| (Grease) Lubrication Speed | 2800 r/min |
| Basic dynamic load rating (C) | 151 kN |
| Basic static load rating (C0) | 197 kN |