



Bearing No. BE30

m	0,37 kg / Weight
d	30 mm
A	21 mm
B	16 mm
b	1,9 mm / Tolerance: +0,3
Noun	Bearing
Bore	1.181 Inch 30 Millimeter
UNSPSC	31171536
Category	Insert Bearings
Seal Type	Double Lip Contact
Snap Ring	Yes
Inventory	0.0
Size (mm)	30x72x21
Width (mm)	21
Weight / LBS	0.816
C _r	20700 N / Dynamic load rating (radial)
C ₁	14,4 mm / Tolerance: +0,2
Inch - Metric	Metric
Product Group	B00308
Relubricatable	No
Other Features	Single Row With Steel Aligning Ring Metric
Keyword String	Insert
Bearing number	BE30
C _{0r}	11300 N / Static load rating (radial)
Mounting Method	Shaft Mount
Rolling Element	Ball Bearing

Outside Diameter	2.835 Inch 72 Millimeter
Manufacturer URL	http://www.ina.com
Long Description	30MM Bore; Narrow Inner Ring; Ball Bearing; 16MM Length Thru Bore; 16MM Outer Race Width; 72MM Outside Diameter; Not Relubricatable; Double Lip Contact Seal; Shaft Mount Mounting Method; Yes Snap Ring
Length Thru Bore	0.63 Inch 16 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Weight / Kilogram	0.37
Manufacturer Name	SCHAEFFLER GROUP
Bore Diameter (mm)	30
Outer Race Profile	Spherical
Inner Race Profile	Narrow Inner Ring
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
D - 72 mm / DIN 620-2	72 mm / DIN 6202
Harmonized Tariff Code	8482.10.50.00
Manufacturer Item Number	BE30
- 206-NPP-B / Designation bearing	206NPPB / Designation bearing
D ₁ - 68,8 mm / Tolerance: -0,5	68,8 mm / Tolerance: 0,5