



Bearing No. 629-2RSH

D	26 mm
d	9 mm
B	8 mm
C	8 mm
D1	22,6 mm
D2	0,3 mm
d1	– mm
d2	13 mm
Bore	0.354 Inch 9 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,02 Kg
r2 min.	11,4 mm
r1 min.	11,4 mm
da min.	12,5 mm
Da max.	23,6 mm
ra max.	0,3 mm
series:	62
Category	Single Row Ball Bearing
Inventory	0.0
Size (mm)	9x26x8
Snap Ring	No
Enclosure	2 Seals
Width (mm)	8
bore type:	Round
Weight / LBS	0.048
Mass bearing	0.02 kg
maximum rpm:	19000 RPM
Product Group	B00308
closure type:	Double Sealed

Cage Material	Steel
Inch - Metric	Metric
bore diameter:	9 mm
overall width:	8 mm
Keyword String	Ball
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	629-2RSH
Enclosure Type	Contact Seal
Limiting speed	19000 r/min
Other Features	Deep Groove NBR Seal
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Reference speed	– r/min
finish/coating:	Uncoated
Long Description	9MM Bore; 26MM Outside Diameter; 8MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; Co
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.skf.com
Outside Diameter	1.024 Inch 26 Millimeter
Outer Race Width	0.315 Inch 8 Millimeter
outer ring width:	8 mm
precision rating:	Not Rated
outside diameter:	26 mm
Manufacturer Name	SKF

Weight / Kilogram	0.022
Bore Diameter (mm)	9
d _a min.	11.4 mm
D _a max.	23.6 mm
Internal Clearance	C0-Medium
d _a max.	12.5 mm
r _a max.	0.3 mm
internal clearance:	C0
Outer Diameter (mm)	26
Minimum Buy Quantity	N/A
r _{1,2} min.	0.3 mm
static load capacity:	1.96 kN
d ₂ ?	12.55 mm
row type & fill slot:	Single Row Non-Fill Slot
D ₂ ?	22.6 mm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	4.75 kN
Fatigue load limit (Pu)	0,083
Calculation factor (f0)	12
Manufacturer Item Number	629-2RSH
Internal Special Features	No
Basic dynamic load rating C	4.75 kN
operating temperature range:	-40 to +210 °F
Basic dynamic load rating (C)	4,75 kN
Basic static load rating (C0)	1,96 kN
Maximum Capacity / Filling Slot	No
Fatigue load limit P _u	0.083 kN

Calculation factor k_r	0.025
Calculation factor f_0	12
Basic static load rating C_0	1.96 kN