



**Bearing No. NN3032KC1NAP4**

D	240 mm
d	160 mm
B	60 mm
C	60 mm
Noun	Bearing
Bore	6.299 Inch   160 Millimeter
Width	2.362 Inch   60 Millimeter
UNSPSC	31171547
series:	NN30K
Profile	Complete with Outer and Inner Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
flanges:	(3) Inner Ring
Snap Ring	No
Separable	Outer Ring - Both Sides
Size (mm)	160x240x60
Inventory	0.0
bore type:	Tapered 1:12
Width (mm)	60
maximum rpm:	2900 rpm
Weight / LBS	20.023
Bore Profile	Tapered
Cage Material	Brass
Product Group	B04270
closure type:	Open
Inch - Metric	Metric
cage material:	High Strength, 2 piece, Machined Brass

overall width:	60 mm
bore diameter:	160 mm
fillet radius:	2.1 mm
Bearing number	NN3032KC1NAP4
Relubricatable	Yes
Other Features	3 Rib Inner Ring   Plain Outer Ring   Precision Bearing   Cage on Inner Ring OD
finish/coating:	Uncoated
Precision Class	ABEC 7   ISO P4
number of rows:	2
Rolling Element	Cylindrical Roller Bearing
Long Description	160MM Bore; Tapered Bore Profile; 240MM Outside Diameter; 60MM Width; Brass Cage Material; ABEC 7   ISO P4; Double Row; Outer Ring - Both Sides Separable; No Snap Ring; Relubricatable; C1NA Internal
Outside Diameter	9.449 Inch   240 Millimeter
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
outer ring width:	60 mm
Manufacturer Name	NTN
Weight / Kilogram	9.09
precision rating:	ISO Class 4
bearing material:	Hardened Alloy Steel
outside diameter:	240 mm
Internal Clearance	C1NA
Bore Diameter (mm)	160
internal clearance:	C1NA

Outer Diameter (mm)	240
Minimum Buy Quantity	N/A
resistance features:	Clean Room, Vacuum
static load capacity:	660000 N
dynamic load capacity:	375000 N
Harmonized Tariff Code	8482.50.00.00
Manufacturer Item Number	NN3032KC1NAP4
Number of Rows of Rollers	Double Row
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C