



Bearing No. NN3024-AS-K-M-SP

| | |
|--------------------|--|
| E | 165 mm |
| d | 120 mm |
| D | 180 mm |
| B | 46 mm |
| m | 3,94 kg / Weight |
| s | 3,1 mm / Axial displacement facility from central position |
| Size (mm) | 120x180x46 |
| Width (mm) | 46 |
| d_s | 3,2 mm |
| C_r | 232000 N / Dynamic load rating (radial) |
| d_1 | 142,6 mm |
| n_s | 6,5 mm |
| C_{0r} | 390000 N / Static load rating (radial) |
| Bearing number | NN3024-AS-K-M-SP |
| C_{ur} | 57000 N / Fatigue limit load, radial |
| r_{min} | 2 mm |
| $n_{G\ OI}$ | 5000 1/min / Limiting speed for minimal quantity oil lubrication |
| $d_{a\ min}$ | 129 mm |
| $r_{a\ max}$ | 2 mm |
| $D_{b\ min}$ | 167 mm |
| $D_{a\ max}$ | 171 mm |
| Bore Diameter (mm) | 120 |
| $n_{G\ Fett}$ | 4300 1/min / Limiting speed for grease |

| | |
|---------------------|-------------|
| | lubrication |
| Outer Diameter (mm) | 180 |