




Bearing No. 6304-2Z/VA228

D	52 mm
d	20 mm
B	15 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Metal Shields
Size (mm)	52x20x15
Snap Ring	No
Width (mm)	15
Mass bearing	0.15 kg
Weight / LBS	0.32
Inch - Metric	Metric
Cage Material	Graphite
Product Group	B00308
D ₂	44.71 mm
d ₁	30.35 mm
Other Features	Deep Groove Extreme Temperature Variant
Keyword String	Ball
Bearing number	6304-2Z/VA228
Limiting speed	250 r/min
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.skf.com
Outside Diameter	2.047 Inch 52 Millimeter
Inner Race Width	0 Inch 0 Millimeter

Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Coronet Cage Internal Special Features; C0-Medium Internal Clear
Outer Race Width	0.591 Inch 15 Millimeter
Weight / Kilogram	0.152
Manufacturer Name	SKF
d _a min.	27 mm
Internal Clearance	C0-Medium
d _a max.	30.3 mm
D _a max.	45 mm
r _a max.	1 mm
Bore Diameter (mm)	52
Outer Diameter (mm)	20
r _{1,2} min.	1.1 mm
Minimum Buy Quantity	N/A
d _a - min.	27 mm
d _a - max.	30.3 mm
D _a - max.	45 mm
r _a - max.	1 mm
d ₁ ?	30.35 mm
D ₂ ?	44.71 mm
Harmonized Tariff Code	8482.10.50.68
r _{1,2} - min.	1.1 mm
Limiting temperature - T	350 °C
Internal Special Features	Coronet Cage
Basic dynamic load rating C	16.8 kN

Limiting temperature T max.	350 °C
Basic dynamic load rating - C	16.8 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C ₀	7.8 kN
Basic static load rating - C ₀	7.8 kN