



Bearing No. 6304DDU

r	1.1
d	20 mm
D	52 mm
B	15 mm
C	15 mm
D_	52
C0	7.9
Z_	7
ra	1
fo	12.4
B_	15
DI_	26.475
SRI	4.81
SRE	5
DE_	45.525
DA_	9.525
D_a	45.5
KBRG	6161
SBRG	3
SRIN	0
bomp	0
SREX	0.04
yobi	6304DDU
SRIX	0.02
Bore	0.787 Inch 20 Millimeter
SDM_	36
SREN	0
mass	0.145
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	26.5
ALPHA_	0
r min.	1,1 mm
Weight	0,145 Kg
C_conv	15900
da max	28 mm
Da max.	45,5 mm
ra max.	1 mm
GRS rpm	10000
da min.	26,5 mm
hidYobi	6304DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	20x52x15
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	15
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.3197
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6304DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.591 Inch 15

	Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.145
Internal Clearance	C0-Medium
Bore Diameter (mm)	20
Outer Diameter (mm)	52
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6304DDU
Internal Special Features	No
(Grease) Lubrication Speed	10 000 r/min
Basic static load rating (C0)	7,9 kN
Basic dynamic load rating (C)	15,9 kN
Maximum Capacity / Filling Slot	No