




Bearing No. 6304LLB

C	15 mm
d	20 mm
D	52 mm
B	15 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
Weight	0,144 Kg
da max	28,5 mm
UNSPSC	31171504
r min.	1,1 mm
da min.	26,5 mm
ra max.	1 mm
series:	63
Da max.	45,5 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	20x52x15
Inventory	0.0
Snap Ring	No
Width (mm)	15
bore type:	Round
maximum rpm:	17000 RPM
Weight / LBS	0.32
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	20 mm
Keyword String	Ball

overall width:	15 mm
cage material:	Steel
fillet radius:	1.1 mm
Bearing number	6304LLB
Enclosure Type	Non-Contact Seal
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	2.047 Inch 52 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
bearing material:	High Carbon Chrome Steel
outer ring width:	15 mm
inner ring width:	15 mm
Manufacturer Name	NTN
Weight / Kilogram	0.145
precision rating:	ISO Class 0
outside diameter:	52 mm
Bore Diameter (mm)	20
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	52
internal clearance:	CN
Minimum Buy Quantity	N/A

static load capacity:	7900 N
maximum rpm (grease):	14000 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	15900 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6304LLB/5C
Internal Special Features	No
(Grease) Lubrication Speed	14 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	15,9 kN
Basic static load rating (C0)	7,9 kN
Maximum Capacity / Filling Slot	No