



Bearing No. 6304LLU

D	52 mm
d	20 mm
B	15 mm
C	15 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
da max	28,5 mm
UNSPSC	31171504
Weight	0,144 Kg
r min.	1,1 mm
da min.	26,5 mm
Da max.	45,5 mm
ra max.	1 mm
series:	63
Category	Single Row Ball Bearing
Inventory	0.0
Size (mm)	20x52x15
Enclosure	2 Seals
Snap Ring	No
bore type:	Round
Width (mm)	15
Weight / LBS	0.317
maximum rpm:	17000 RPM
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Other Features	Deep Groove Double Lip Friction Nitrile

	Rubber Seal -20 To 120 Deg C
Enclosure Type	Contact Seal
Bearing number	6304LLU
bore diameter:	20 mm
overall width:	15 mm
cage material:	Steel
fillet radius:	1.1 mm
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Reference speed	10 000 r/min
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.ntnamerica.com
inner ring width:	15 mm
Weight / Kilogram	0.145
outer ring width:	15 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
outside diameter:	52 mm

precision rating:	ISO Class 0
Bore Diameter (mm)	20
Internal Clearance	C0-Medium
Outer Diameter (mm)	52
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	7900 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	10000 rpm
dynamic load capacity:	15900 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6304LLU
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	15,9 kN
Basic static load rating (C0)	7,9 kN
Maximum Capacity / Filling Slot	No