



**Bearing No. NN3005KC1NAP4**

D	47 mm
d	25 mm
B	16 mm
C	16 mm
Noun	Bearing
Bore	0.984 Inch   25 Millimeter
Width	0.63 Inch   16 Millimeter
UNSPSC	31171547
series:	NN30K
Profile	Complete with Outer and Inner Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
flanges:	(3) Inner Ring
Snap Ring	No
Separable	Outer Ring - Both Sides
Size (mm)	25x47x16
Inventory	0.0
bore type:	Tapered 1:12
Width (mm)	16
maximum rpm:	17000 rpm
Weight / LBS	0.265
Bore Profile	Tapered
Cage Material	Brass
Product Group	B04270
closure type:	Open
Inch - Metric	Metric
cage material:	High Strength, 2 piece, Machined Brass

overall width:	16 mm
bore diameter:	25 mm
fillet radius:	0.6 mm
Bearing number	NN3005KC1NAP4
Relubricatable	Yes
Other Features	3 Rib Inner Ring   Plain Outer Ring   Precision Bearing   Cage on Inner Ring OD
finish/coating:	Uncoated
Precision Class	ABEC 7   ISO P4
number of rows:	2
Rolling Element	Cylindrical Roller Bearing
Long Description	25MM Bore; Tapered Bore Profile; 47MM Outside Diameter; 16MM Width; Brass Cage Material; ABEC 7   ISO P4; Double Row; Outer Ring - Both Sides Separable; No Snap Ring; Relubricatable; C1NA Internal Cl
Outside Diameter	1.85 Inch   47 Millimeter
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
outer ring width:	16 mm
Manufacturer Name	NTN
Weight / Kilogram	0.12
precision rating:	ISO Class 4
bearing material:	Hardened Alloy Steel
outside diameter:	47 mm
Internal Clearance	C1NA
Bore Diameter (mm)	25
internal clearance:	C1NA

Outer Diameter (mm)	47
Minimum Buy Quantity	N/A
resistance features:	Clean Room, Vacuum
static load capacity:	30000 N
dynamic load capacity:	25800 N
Harmonized Tariff Code	8482.50.00.00
Manufacturer Item Number	NN3005KC1NAP4
Number of Rows of Rollers	Double Row
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C