



**Bearing No. 88506**

C	24,000 mm
d	30,000 mm
B	24,000 mm
D	62,000 mm
Bore	1.181 Inch   30 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	88
Category	Single Row Ball Bearing
Size (mm)	30x62x24
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	24,000
bore type:	Round
Weight / LBS	0.571
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
bore diameter:	30 mm
overall width:	24 mm
Keyword String	Ball
fillet radius:	1 mm
cage material:	Steel
Bearing number	88506
Other Features	Deep Groove   Felt Seal   Shell Alvania Prelubricated
Enclosure Type	Contact Seal

finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Inner Race Width	0.945 Inch   24 Millimeter
Outer Race Width	0.63 Inch   16 Millimeter
Outside Diameter	2.441 Inch   62 Millimeter
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; Extended Inner Ring Internal Special Features; C0-Medium Internal Clearance
outer ring width:	16 mm
inner ring width:	24 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	62 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	30,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	62,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot

maximum rpm (grease):	7300 rpm
static load capacity:	11300 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	19600 N
Internal Special Features	Extended Inner Ring
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No