



Bearing No. 6304ZZNR

D	52,000 mm
C	15,000 mm
B	15,000 mm
d	20,000 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	63
Category	Single Row Ball Bearing
Size (mm)	20x52x15
Enclosure	2 Metal Shields
Snap Ring	Yes
Inventory	0.0
Width (mm)	15,000
bore type:	Round
maximum rpm:	17000 RPM
Weight / LBS	0.317
Cage Material	Steel
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Bearing number	6304ZZNR
bore diameter:	20 mm
overall width:	15 mm
fillet radius:	1.1 mm
cage material:	Steel
Keyword String	Ball
Rolling Element	Ball Bearing
finish/coating:	Uncoated

Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	2.047 Inch 52 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Weight / Kilogram	0.143
outer ring width:	15 mm
inner ring width:	15 mm
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	52 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	20,000
Internal Clearance	C3-Loose
Outer Diameter (mm)	52,000
snap ring included:	With Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	7900 N
maximum rpm (grease):	14000 rpm
dynamic load capacity:	15900 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item	6304ZZNR/2A

Number	
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No