



Bearing No. NN 3068 K/SPW33

S	10,9 mm
K	9 mm
d	340 mm
D	520 mm
B	133 mm
C	133 mm
b	16,7 mm
E	473 mm
d1	408 mm
dh	– mm
s max.	10.9 mm
Weight	94,5 Kg
Da min	477 mm
ra max.	4 mm
Da max.	502 mm
da min.	358 mm
r1 min.	5 mm
r4 min.	3 mm
r3 min.	3 mm
r2 min.	5 mm
Size (mm)	340x520x133
Width (mm)	133
Mass bearing	94.5 kg
d <sub>1</sub>	408 mm
Bearing number	NN 3068 K/SPW33
Bore Diameter (mm)	340
r <sub>a</sub> max.	4 mm
D <sub>a</sub> max.	502 mm
D <sub>a</sub> min.	477 mm
d <sub>a</sub> min.	358 mm

Outer Diameter (mm)	520
$r_{3,4}$ min.	3 mm
$r_{1,2}$ min.	5 mm
(Oil) Lubrication Speed	1 600 r/min
(Grease) Lubrication Speed	1 400 r/min
Basic dynamic load rating C	1650 kN
Basic dynamic load rating (C)	1 650 kN
Basic static load rating (C <sub>0</sub> )	3 250 kN
Fatigue load limit P <sub>u</sub>	290 kN
Basic static load rating C <sub>0</sub>	3250 kN
Attainable speed for grease lubrication	1400 r/min
Attainable speed for oil-air lubrication	1600 r/min