



Bearing No. NN 3080 K/SPW33

S	12,4 mm
K	9 mm
d	400 mm
D	600 mm
B	148 mm
C	148 mm
b	16,7 mm
E	549 mm
d1	475 mm
dh	– mm
s max.	12.4 mm
Weight	135 Kg
Da min	553 mm
ra max.	4 mm
Da max.	582 mm
da min.	418 mm
r1 min.	5 mm
r4 min.	2,5 mm
r3 min.	2,5 mm
r2 min.	5 mm
Size (mm)	400x600x148
Width (mm)	148
Mass bearing	135 kg
d ₁	475 mm
Bearing number	NN 3080 K/SPW33
Bore Diameter (mm)	400
r _a max.	4 mm
D _a max.	582 mm
D _a min.	553 mm
d _a min.	418 mm

Outer Diameter (mm)	600
$r_{3,4}$ min.	2.5 mm
$r_{1,2}$ min.	5 mm
(Oil) Lubrication Speed	1 400 r/min
(Grease) Lubrication Speed	1 200 r/min
Basic dynamic load rating C	2160 kN
Basic dynamic load rating (C)	2 160 kN
Basic static load rating (C ₀)	4 500 kN
Fatigue load limit P _u	380 kN
Basic static load rating C ₀	4500 kN
Attainable speed for grease lubrication	1200 r/min
Attainable speed for oil-air lubrication	1400 r/min