



Bearing No. NN 3084 K/SPW33

S	12,4 mm
K	9 mm
d	420 mm
D	620 mm
B	150 mm
C	150 mm
b	16,7 mm
E	569 mm
d1	495 mm
dh	– mm
s max.	12.4 mm
Weight	140 Kg
Da min	574 mm
ra max.	4 mm
Da max.	602 mm
da min.	438 mm
r1 min.	5 mm
r4 min.	2 mm
r3 min.	2 mm
r2 min.	5 mm
Size (mm)	420x620x150
Width (mm)	150
Mass bearing	140 kg
d <sub>1</sub>	495 mm
Bearing number	NN 3084 K/SPW33
Bore Diameter (mm)	420
r <sub>a</sub> max.	4 mm
D <sub>a</sub> max.	602 mm
D <sub>a</sub> min.	574 mm
d <sub>a</sub> min.	438 mm

Outer Diameter (mm)	620
$r_{3,4}$ min.	2 mm
$r_{1,2}$ min.	5 mm
(Oil) Lubrication Speed	1 300 r/min
(Grease) Lubrication Speed	1 100 r/min
Basic dynamic load rating C	2120 kN
Basic dynamic load rating (C)	2 120 kN
Basic static load rating (C <sub>0</sub> )	4 500 kN
Fatigue load limit P <sub>u</sub>	380 kN
Basic static load rating C <sub>0</sub>	4500 kN
Attainable speed for grease lubrication	1100 r/min
Attainable speed for oil-air lubrication	1300 r/min