



Bearing No. 6305VV

D	62 mm
d	25 mm
B	17 mm
C	17 mm
r	1.1
Z_	8
B_	17
D_	62
ra	1
C0	11.2
fo	13.2
DI_	34.181
SRI	5.21
D_a	55.5
DE_	54.819
DA_	10.319
SRE	5.47
SRIN	0
SBRG	3
yobi	6305VV
SDM_	44.5
SREX	0.05
KBRG	6151
bomp	0
mass	0.235
Bore	0.984 Inch   25 Millimeter
SRIX	0.025
SREN	0
Noun	Bearing

ALPHA_	0
da min	31.5
LangID	1
r min.	1,1 mm
UNSPSC	31171504
C_conv	20600
da max	36 mm
Weight	0,235 Kg
hidYobi	6305VV
Da max.	55,5 mm
da min.	31,5 mm
ra max.	1 mm
GRS rpm	11000
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Size (mm)	25x62x17
Width (mm)	17
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.232
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6305VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outside Diameter	2.441 Inch   62 Millimeter
Outer Race Width	0.669 Inch   17

	Millimeter
Long Description	25MM Bore; 62MM Outside Diameter; 17MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Weight / Kilogram	0.23
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	25
Outer Diameter (mm)	62
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6305VV
Internal Special Features	No
(Grease) Lubrication Speed	11 000 r/min
Basic static load rating (C0)	11,2 kN
Basic dynamic load rating (C)	20,6 kN
Maximum Capacity / Filling Slot	No