



Bearing No. 6305LLU

C	17 mm
d	25 mm
D	62 mm
B	17 mm
Bore	0.984 Inch 25 Millimeter
Noun	Bearing
Weight	0,232 Kg
da max	35 mm
UNSPSC	31171504
r min.	1,1 mm
da min.	31,5 mm
ra max.	1 mm
series:	63
Da max.	55,5 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	25x62x17
Inventory	0.0
Snap Ring	No
Width (mm)	17
bore type:	Round
maximum rpm:	1400 RPM
Weight / LBS	0.508
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	25 mm
Keyword String	Ball

overall width:	17 mm
cage material:	Steel
fillet radius:	1.1 mm
Bearing number	6305LLU
Enclosure Type	Contact Seal
Reference speed	8 100 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	2.441 Inch 62 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Long Description	25MM Bore; 62MM Outside Diameter; 17MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.669 Inch 17 Millimeter
outside diameter:	62 mm
precision rating:	ISO Class 0
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.23
inner ring width:	17 mm
outer ring width:	17 mm
Manufacturer Name	NTN
Bore Diameter (mm)	25
Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	62

Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	8100 rpm
static load capacity:	10900 N
dynamic load capacity:	21200 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6305LLU/5CQP
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	10,9 kN
Basic dynamic load rating (C)	21,2 kN
Maximum Capacity / Filling Slot	No