



Bearing No. NKXR 15 Z

d	15 mm
F	15 mm
D	24 mm
C	23 mm
Category	Roller Bearings
Inventory	0.0
Size (mm)	24x15x23
Inner ring	IR 12x15x16
Width (mm)	23
Mass bearing	0.045 kg
C ₂	6.5 mm
C ₁	9 mm
D ₂	29.2 mm
C ₂	6.5 mm
C ₁	9 mm
F _w	15 mm
d _i	12 mm
F _w	15 mm
B _i	16 mm
Product Group	B04144
d _i	12 mm
B _i	16 mm
D ₂	29.2 mm
Bearing number	NKXR 15 Z
Limiting speed	8500 r/min
Reference speed	4300 r/min
Manufacturer Name	SKF
Weight / Kilogram	0.05
Bore Diameter (mm)	24

r_b max.	0.3 mm
r_a max.	0.3 mm
d_a min.	23.7 mm
Outer Diameter (mm)	15
d_a - min.	23.7 mm
$r_{1,2}$ min.	0.3 mm
r_a - max.	0.3 mm
Minimum Buy Quantity	N/A
r_b - max.	0.3 mm
$r_{1,2}$ - min.	0.3 mm
Minimum axial load factor A	0.000058
Basic dynamic load rating, axial direction C	11.2 kN
Basic dynamic load rating, radial direction C	11 kN
Basic dynamic load rating, axial direction - C	11.2 kN
Basic dynamic load rating, radial direction - C	11 kN
Fatigue load limit, axial direction P_u	2.45 kN
Fatigue load limit, radial direction P_u	1.66 kN
Fatigue load limit, axial direction - P_u	2.4 kN
Fatigue load limit, radial direction - P_u	1.7 kN
Basic static load rating, axial direction C_0	27 kN
Basic static load rating, radial direction C_0	14 kN
Basic static load rating, axial direction - C_0	27 kN
Basic static load rating,	14 kN

radial direction - C ₀	
-----------------------------------	--