



**Bearing No. NKXR 17**

d	17 mm
F	17 mm
D	26 mm
C	25 mm
Category	Bearings
Inventory	0.0
Size (mm)	26x17x25
Inner ring	IR 14x17x17
Width (mm)	25
Mass bearing	0.05 kg
C <sub>2</sub>	8 mm
C <sub>1</sub>	9 mm
D <sub>1</sub>	30.1 mm
C <sub>2</sub>	8 mm
C <sub>1</sub>	9 mm
F <sub>w</sub>	17 mm
d <sub>i</sub>	14 mm
F <sub>w</sub>	17 mm
B <sub>i</sub>	17 mm
Product Group	B04144
d <sub>i</sub>	14 mm
B <sub>i</sub>	17 mm
D <sub>1</sub>	30.1 mm
Bearing number	NKXR 17
Limiting speed	8500 r/min
Reference speed	4300 r/min
Manufacturer Name	SKF
Weight / Kilogram	0
Bore Diameter (mm)	26

$r_b$ max.	0.3 mm
$r_a$ max.	0.3 mm
$d_a$ min.	25.7 mm
Outer Diameter (mm)	17
$d_a$ - min.	25.7 mm
$r_{1,2}$ min.	0.3 mm
$r_a$ - max.	0.3 mm
Minimum Buy Quantity	N/A
$r_b$ - max.	0.3 mm
$r_{1,2}$ - min.	0.3 mm
Minimum axial load factor A	0.000079
Basic dynamic load rating, axial direction C	12.2 kN
Basic dynamic load rating, radial direction C	12.1 kN
Basic dynamic load rating, axial direction - C	12.2 kN
Basic dynamic load rating, radial direction - C	12.1 kN
Fatigue load limit, axial direction $P_u$	2.85 kN
Fatigue load limit, radial direction $P_u$	1.96 kN
Fatigue load limit, axial direction - $P_u$	2.8 kN
Fatigue load limit, radial direction - $P_u$	2 kN
Basic static load rating, axial direction $C_0$	31.5 kN
Basic static load rating, radial direction $C_0$	16.6 kN
Basic static load rating, axial direction - $C_0$	31.5 kN
Basic static load rating,	16.6 kN

radial direction - C <sub>0</sub>	
-----------------------------------	--