



Bearing No. NJG2308VH

S	2,4 mm
d	40 mm
D	90 mm
B	33 mm
C	33 mm
F	51,15 mm
D1	75,2 mm
d1	57,6 mm
Weight	1 Kg
series:	NJG23
ra max.	1,5 mm
db max.	49 mm
Da max.	81 mm
da min.	49 mm
r4 min.	- mm
r3 min.	- mm
r2 min.	1,5 mm
r1 min.	1,5 mm
das rec.	54,4 mm
flanges:	(2) Outer Ring, (1) Inner Ring
Size (mm)	40x90x33
Width (mm)	33
bore type:	Straight
maximum rpm:	3600 RPM
closure type:	Open
overall width:	33 mm
cage material:	No Cage
Bearing number	NJG2308VH
bore diameter:	40 mm

Limiting speed	3600 r/min
fillet radius:	1.5 mm
Reference speed	3000 r/min
finish/coating:	Uncoated
number of rows:	1
ring separation:	Non-Separable
outside diameter:	90 mm
precision rating:	Not Rated
outer ring width:	33 mm
Bore Diameter (mm)	40
Outer Diameter (mm)	90
internal clearance:	C0
static load capacity:	156 kN
dynamic load capacity:	145 kN
Fatigue load limit (Pu)	20
operating temperature range:	Maximum of +300 °F
Basic static load rating (C0)	156 kN
Basic dynamic load rating (C)	145 kN