



### Bearing No. 6307LLU

D	80 mm
d	35 mm
B	21 mm
C	21 mm
Noun	Bearing
Bore	1.378 Inch   35 Millimeter
da max	47 mm
UNSPSC	31171504
r min.	1,5 mm
Weight	0,457 Kg
da min.	43 mm
Da max.	72 mm
ra max.	1,5 mm
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Size (mm)	35x80x21
Snap Ring	No
bore type:	Round
Width (mm)	21
Weight / LBS	1.021
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricated
bore diameter:	35 mm

Keyword String	Ball
overall width:	21 mm
cage material:	Steel
fillet radius:	1.5 mm
Bearing number	6307LLU
Enclosure Type	Contact Seal
Rolling Element	Ball Bearing
Reference speed	6 000 r/min
finish/coating:	Uncoated
Precision Class	ABEC 1   ISO P0
Outside Diameter	3.15 Inch   80 Millimeter
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outer Race Width	0.827 Inch   21 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Long Description	35MM Bore; 80MM Outside Diameter; 21MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
outer ring width:	21 mm
inner ring width:	21 mm
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Weight / Kilogram	0.462
Manufacturer Name	NTN
outside diameter:	80 mm
Bore Diameter (mm)	35
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring

Outer Diameter (mm)	80
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	19100 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	6000 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	33500 N
Manufacturer Item Number	6307LLU/5C
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	19,1 kN
Basic dynamic load rating (C)	33,5 kN
Maximum Capacity / Filling Slot	No