



**Bearing No. 6307LLUNR**

D	80,000 mm
d	35,000 mm
B	21,000 mm
C	21,000 mm
Noun	Bearing
Bore	1.378 Inch   35 Millimeter
UNSPSC	31171504
series:	63
Category	Single Row Ball Bearing
Snap Ring	Yes
Enclosure	2 Seals
Size (mm)	35x80x21
Inventory	0.0
bore type:	Round
Width (mm)	21,000
maximum rpm:	10000 RPM
Weight / LBS	1.01
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
fillet radius:	1.5 mm
overall width:	21 mm
bore diameter:	35 mm
Keyword String	Ball
cage material:	Steel
Bearing number	6307LLUNR
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   With Snap

	Ring   -20 To 120 Deg C   Shell Alvania Prelubricated
Enclosure Type	Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	3.15 Inch   80 Millimeter
Long Description	35MM Bore; 80MM Outside Diameter; 21MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.827 Inch   21 Millimeter
precision rating:	ISO Class 0
outside diameter:	80 mm
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
Weight / Kilogram	0
inner ring width:	21 mm
outer ring width:	21 mm
Bore Diameter (mm)	35,000
Internal Clearance	C0-Medium
snap ring included:	With Snap Ring
Outer Diameter (mm)	80,000
internal clearance:	CN

Minimum Buy Quantity	N/A
maximum rpm (grease):	6000 rpm
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	19100 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	33500 N
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No