



Bearing No. 6926NR

f	1.7 mm
a	3.7 mm
b	1.9 mm
d	130 mm
D	180 mm
B	24 mm
C	24 mm
D2	186.5 mm
D1	176.8 mm
r1	0.5 mm
Width	24 mm
r min.	1.5 mm
Weight	1.81 Kg
r1 min.	0.5 mm
b (min)	1.9 mm
a (max)	3.7 mm
Da (max)	173 mm
Dx (min)	188 mm
ra (max)	1.5 mm
da (min)	137 mm
D1 (max)	176.8 mm
Cy (max)	5.1 mm
Factor fo	16.4
Enclosure	Snap Ring Groove with Snap Ring
Bore Size	130 mm
Size (mm)	130x180x24
Bore Type	Cylindrical Bore
Width (mm)	24
Configuration	Single Row

Bearing number	6926NR
Snap Ring Width	1.7 mm
Radial Clearance	0.018 to 0.048 mm
Outside Diameter	180 mm
Static Load Rating	67,000 N
Bore Diameter (mm)	130
Outer Diameter (mm)	180
Dynamic Load Rating	65,000 N
Limiting Speed - Oil	4,200 rpm
Fillet Radius/Chamfer	1.5 mm
Limiting Speed - Grease	3,500 rpm
(Grease) Lubrication Speed	3400 r/min
Snap Ring Outside Diameter	186.5 mm
Basic static load rating (C0)	67 kN
Basic dynamic load rating (C)	65 kN