



Bearing No. 6926ZZ

C	24,000 mm
d	130,000 mm
B	24,000 mm
D	180,000 mm
Noun	Bearing
Bore	5.118 Inch 130 Millimeter
UNSPSC	31171504
series:	69
Category	Single Row Ball Bearing
Size (mm)	130x180x24
Enclosure	2 Metal Shields
Snap Ring	No
Inventory	0.0
Width (mm)	24,000
bore type:	Round
maximum rpm:	3500 RPM
Weight / LBS	3.395
Cage Material	Steel
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Bearing number	6926ZZ
bore diameter:	130 mm
overall width:	24 mm
fillet radius:	1.5 mm
cage material:	Steel
Keyword String	Ball
Other Features	Deep Groove Shell Alvania Prelubricated
Precision Class	ABEC 1 ISO P0

Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	130MM Bore; 180MM Outside Diameter; 24MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Outer Race Width	0.945 Inch 24 Millimeter
Outside Diameter	7.087 Inch 180 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Name	NTN
outer ring width:	24 mm
inner ring width:	24 mm
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	180 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	130,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	180,000
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	67500 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	3500 rpm

dynamic load capacity:	65000 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6926ZZ/2AS
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No