



Bearing No. 6926ZZ

D	180 mm
d	130 mm
B	24 mm
C	24 mm
r	1.5
Z_	18
B_	24
D_	180
ra	1.5
C0	67.5
fo	16.5
DI_	139.919
SRI	7.8
D_a	172
DE_	170.081
DA_	15.081
SRE	7.8
SRIN	-0.03
SBRG	19
yobi	6926ZZ
SDM_	155
SREX	0.03
KBRG	6141
bomp	0
mass	1.57
Bore	5.118 Inch 130 Millimeter
SRIX	0.03
SREN	-0.03
Noun	Bearing

ALPHA_	0
da min	138
LangID	1
r min.	1,5 mm
UNSPSC	31171504
da max	144 mm
C_conv	65000
Weight	1,57 Kg
ra max.	1,5 mm
hidYobi	6926ZZ
GRS rpm	3400
Da max.	172 mm
da min.	138 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	130x180x24
Enclosure	2 Metal Shields
Inventory	0.0
Width (mm)	24
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	3.4619
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6926ZZ
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.945 Inch 24 Millimeter
Outside Diameter	7.087 Inch 180

	Millimeter
Long Description	130MM Bore; 180MM Outside Diameter; 24MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; St
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Weight / Kilogram	1.78
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	130
Outer Diameter (mm)	180
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	3 400 r/min
Basic static load rating (C0)	67,5 kN
Basic dynamic load rating (C)	65 kN
Maximum Capacity / Filling Slot	No