



Bearing No. 6928N

a	3,7 mm
r	1.5
d	140 mm
D	190 mm
B	24 mm
C	24 mm
b	1,9 mm
fo	16.6
B_	24
ra	1.5
C0	72
D1	186,8 mm
D_	190
Z_	19
rn	0,5 mm
ro	0.6
DE_	180.081
SRI	7.8
D_a	182
DA_	15.081
SRE	7.8
DI_	149.919
yobi	6928N
mass	1.67
SBRG	19
bomp	0
KBRG	6101
SREX	0.03
SREN	-0.03
SRIN	-0.03

SDM_	165
SRIX	0.03
ALPHA_	0
r min.	1,5 mm
C_conv	66500
da max	153,5 mm
da min	148
Weight	1,67 Kg
LangID	1
ra max.	1,5 mm
Da max.	182 mm
Oil rpm	3800
da min.	148 mm
r0 max.	0,6 mm
hidYobi	6928N
GRS rpm	3200
hidTable	ecat_NSRDGB
Size (mm)	140x190x24
Prod_Type3	DGBB_SR_N_OT
Width (mm)	24
Bearing number	6928N
Bore Diameter (mm)	140
Outer Diameter (mm)	190
(Oil) Lubrication Speed	3 800 r/min
(Grease) Lubrication Speed	3 200 r/min
Basic dynamic load rating (C)	66,5 kN
Basic static load rating (C0)	72 kN