



## Bearing No. 6926

r	1.5
d	130 mm
D	180 mm
B	24 mm
C	24 mm
fo	16.5
C0	67.5
B_	24
Z_	18
ra	1.5
D_	180
SRI	7.8
DA_	15.081
SRE	7.8
DE_	170.081
DI_	139.919
D_a	172
SREN	-0.03
Bore	5.118 Inch   130 Millimeter
SRIN	-0.03
mass	1.57
bomp	0
Noun	Bearing
yobi	6926
SRIX	0.03
SDM_	155
SREX	0.03
KBRG	6101
SBRG	19

C_conv	65000
ALPHA_	0
Weight	1,57 Kg
da max	144 mm
r min.	1,5 mm
da min	138
UNSPSC	31171504
LangID	1
hidYobi	6926
GRS rpm	3400
Oil rpm	4000
Da max.	172 mm
ra max.	1,5 mm
da min.	138 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	130x180x24
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	24
Prod_Type3	DGBB_SR_OT
Weight / LBS	3.4619
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6926
Keyword String	Ball
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Outside Diameter	7.087 Inch   180 Millimeter

Long Description	130MM Bore; 180MM Outside Diameter; 24MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.945 Inch   24 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Name	NSK
Weight / Kilogram	1.5
Internal Clearance	C0-Medium
Bore Diameter (mm)	130
Outer Diameter (mm)	180
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	4 000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	3 400 r/min
Basic static load rating (C0)	67,5 kN
Basic dynamic load rating (C)	65 kN
Maximum Capacity / Filling Slot	No