



Bearing No. 6926N

a	3,7 mm
r	1.5
d	130 mm
D	180 mm
B	24 mm
C	24 mm
b	1,9 mm
fo	16.5
B_	24
ra	1.5
C0	67.5
D1	176,8 mm
D_	180
Z_	18
rn	0,5 mm
ro	0.6
DE_	170.081
SRI	7.8
D_a	172
DA_	15.081
SRE	7.8
DI_	139.919
yobi	6926N
mass	1.57
SBRG	19
bomp	0
KBRG	6101
SREX	0.03
SREN	-0.03
SRIN	-0.03

SDM_	155
SRIX	0.03
ALPHA_	0
r min.	1,5 mm
C_conv	65000
da max	144 mm
da min	138
Weight	1,57 Kg
LangID	1
ra max.	1,5 mm
Da max.	172 mm
Oil rpm	4000
da min.	138 mm
r0 max.	0,6 mm
hidYobi	6926N
GRS rpm	3400
hidTable	ecat_NS RDGB
Size (mm)	130x180x24
Prod_Type3	DGBB_SR_N_OT
Width (mm)	24
Bearing number	6926N
Bore Diameter (mm)	130
Outer Diameter (mm)	180
(Oil) Lubrication Speed	4 000 r/min
(Grease) Lubrication Speed	3 400 r/min
Basic dynamic load rating (C)	65 kN
Basic static load rating (C0)	67,5 kN