



VA201



ZZ/VA201



ZZ/VA208



ZZ/VA228

Bearing No. 6311/VA201

| | |
|-----------------|---|
| D | 120 mm |
| d | 55 mm |
| B | 29 mm |
| C | 29 mm |
| d1 | 75,3 mm |
| D2 | 104 mm |
| Bore | 2.165 Inch 55 Millimeter |
| Noun | Bearing |
| Weight | 1,35 Kg |
| UNSPSC | 31171504 |
| r1 min. | 2 mm |
| r2 min. | 2 mm |
| Category | Single Row Ball Bearing |
| Enclosure | Open |
| Inventory | 0.0 |
| Snap Ring | No |
| Size (mm) | 55x120x29 |
| Width (mm) | 29 |
| Weight / LBS | 1.35 |
| Mass bearing | 1.37 kg |
| Temperature - | 30 to +250 ° |
| Product Group | B00308 |
| Inch - Metric | Metric |
| Cage Material | Steel |
| Keyword String | Ball |
| Limiting speed | 100 r/min |
| Other Features | Deep Groove Extreme Temperature Variant |
| Bearing number | 6311/VA201 |
| Rolling Element | Ball Bearing |

| | |
|-----------------------------|--|
| Precision Class | ABEC 1 ISO P0 |
| Manufacturer URL | http://www.skf.com |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 1.142 Inch 29 Millimeter |
| Outside Diameter | 4.724 Inch 120 Millimeter |
| Long Description | 55MM Bore; 120MM Outside Diameter; 29MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Polyalkylene Glycol/Graphite Mixture Filled Internal Special Features; C0- |
| Manufacturer Name | SKF |
| Weight / Kilogram | 0 |
| D _a max. | 109 mm |
| Bore Diameter (mm) | 55 |
| r _a max. | 2 mm |
| Internal Clearance | C0-Medium |
| d _a min. | 66 mm |
| Outer Diameter (mm) | 120 |
| Minimum Buy Quantity | N/A |
| r _{1,2} min. | 2 mm |
| D ₂ ? | 103.7 mm |
| d ₁ ? | 75.34 mm |
| Harmonized Tariff Code | 8482.10.50.68 |
| Internal Special Features | Polyalkylene Glycol/Graphite Mixture Filled |
| Basic dynamic load rating C | 74.1 kN |
| Limiting temperature T max. | 250 °C |

| | |
|---|-------|
| Basic static load rating (C0) | 45 kN |
| Maximum Capacity / Filling Slot | No |
| Basic static load rating C ₀ | 45 kN |