



Bearing No. 6915ZZ

D	105 mm
d	75 mm
B	16 mm
C	16 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
Width	16 mm
Weight	0.345 Kg
UNSPSC	31171504
r min.	1 mm
da min.	80 mm
Da max.	100 mm
ra max.	1.0 mm
Category	Single Row Ball Bearing
ra (max)	1 mm
da (min)	80 mm
Da (max)	100 mm
Factor fo	16.5
Size (mm)	75x105x16
Inventory	0.0
Bore Size	75 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Width (mm)	16
Configuration	Single Row
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308

Bearing number	6915ZZ
Other Features	Deep Groove
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Radial Clearance	0.010 to 0.030 mm
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	4.134 Inch 105 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	75MM Bore; 105MM Outside Diameter; 16MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	http://www.nachiamerica.com
Weight / Kilogram	0.345
Manufacturer Name	NACHI
Bore Diameter (mm)	75
Internal Clearance	C0-Medium
Static Load Rating	19,700 N
Outer Diameter (mm)	105
Dynamic Load Rating	20,800 N
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	1 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	6,200 rpm
Manufacturer Item Number	6915ZZBV2S
Internal Special	No

Features	
Basic dynamic load rating (C)	20,8 kN
Basic static load rating (C0)	19,7 kN
Maximum Capacity / Filling Slot	No