



Bearing No. 6915

D	105 mm
d	75 mm
B	16 mm
C	16 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
Width	16 mm
UNSPSC	31171504
r min.	1 mm
Weight	0.345 Kg
Da max.	100 mm
da min.	80 mm
ra max.	1.0 mm
Category	Single Row Ball Bearing
ra (max)	1 mm
da (min)	80 mm
Da (max)	100 mm
Bore Size	75 mm
Bore Type	Cylindrical Bore
Enclosure	Open
Factor fo	16.5
Size (mm)	75x105x16
Snap Ring	No
Inventory	0.0
Width (mm)	16
Weight / LBS	0.76
Product Group	B00308
Inch - Metric	Metric
Configuration	Single Row

Keyword String	Ball
Bearing number	6915
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	75MM Bore; 105MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.63 Inch 16 Millimeter
Radial Clearance	0.010 to 0.030 mm
Outside Diameter	4.134 Inch 105 Millimeter
Manufacturer URL	http://www.nachi.com
Weight / Kilogram	0.345
Manufacturer Name	NACHI
Internal Clearance	C0-Medium
Bore Diameter (mm)	75
Static Load Rating	19,700 N
Dynamic Load Rating	20,800 N
Outer Diameter (mm)	105
Minimum Buy Quantity	N/A
Limiting Speed - Oil	7,200 rpm
Fillet Radius/Chamfer	1 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	6,200 rpm
Internal Special Features	No
(Grease) Lubrication Speed	6200 r/min
Basic dynamic load rating (C)	20,8 kN
Basic static load rating	19,7 kN

(C0)	
Maximum Capacity / Filling Slot	No