



Bearing No. 6913LLU

| | |
|----------------|---|
| D | 90 mm |
| d | 65 mm |
| B | 13 mm |
| C | 13 mm |
| Bore | 2.559 Inch 65 Millimeter |
| Noun | Bearing |
| da max | 71,5 mm |
| UNSPSC | 31171504 |
| Weight | 0,206 Kg |
| r min. | 1 mm |
| Da max. | 85 mm |
| ra max. | 1 mm |
| da min. | 70 mm |
| series: | 69 |
| Category | Single Row Ball Bearing |
| Inventory | 0.0 |
| Snap Ring | No |
| Enclosure | 2 Seals |
| Size (mm) | 65x90x13 |
| Width (mm) | 13 |
| bore type: | Round |
| maximum rpm: | 8200 RPM |
| Weight / LBS | 0.458 |
| Inch - Metric | Metric |
| Cage Material | Steel |
| closure type: | Double Sealed |
| Product Group | B00308 |
| Keyword String | Ball |
| Other Features | Deep Groove Double Lip Friction Nitrile |

| | |
|-------------------|---|
| | Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated |
| Enclosure Type | Contact Seal |
| Bearing number | 6913LLU |
| bore diameter: | 65 mm |
| overall width: | 13 mm |
| fillet radius: | 1 mm |
| cage material: | Steel |
| Rolling Element | Ball Bearing |
| finish/coating: | Uncoated |
| Precision Class | ABEC 1 ISO P0 |
| Reference speed | 4 000 r/min |
| Inner Race Width | 0 Inch 0 Millimeter |
| Outer Race Width | 0.512 Inch 13 Millimeter |
| Long Description | 65MM Bore; 90MM Outside Diameter; 13MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Outside Diameter | 3.543 Inch 90 Millimeter |
| Manufacturer URL | http://www.ntnamerica.com |
| inner ring width: | 13 mm |
| precision rating: | ISO Class 0 |
| outside diameter: | 90 mm |
| Weight / Kilogram | 0.207 |
| bearing material: | High Carbon Chrome Steel |
| Manufacturer Name | NTN |
| outer ring width: | 13 mm |
| | |

| | |
|---------------------------------|----------------------------|
| Bore Diameter (mm) | 65 |
| Internal Clearance | C0-Medium |
| internal clearance: | CN |
| snap ring included: | Without Snap Ring |
| Outer Diameter (mm) | 90 |
| Minimum Buy Quantity | N/A |
| row type & fill slot: | Single Row Non-Fill Slot |
| static load capacity: | 16100 N |
| maximum rpm (grease): | 4000 rpm |
| Harmonized Tariff Code | 8482.10.50.68 |
| dynamic load capacity: | 17400 N |
| Manufacturer Item Number | 6913LLU/2AS |
| Internal Special Features | No |
| manufacturer product page: | Click here |
| operating temperature range: | -40 to 120 °C |
| Basic dynamic load rating (C) | 17,4 kN |
| Basic static load rating (C0) | 16,1 kN |
| Maximum Capacity / Filling Slot | No |