



Bearing No. 6913N

a	2,1 mm
r	1
d	65 mm
D	90 mm
B	13 mm
C	13 mm
b	1,3 mm
fo	16.6
B_	13
ra	1
C0	16.1
D1	87,9 mm
D_	90
Z_	19
rn	0,5 mm
ro	0.4
DE_	84.644
SRI	3.7
D_a	85
DA_	7.144
SRE	3.7
DI_	70.356
yobi	6913N
mass	0.218
SBRG	19
bomp	0
KBRG	6101
SREX	0.02
SREN	-0.02
SRIN	-0.02

SDM_	77.5
SRIX	0.02
ALPHA_	0
r min.	1 mm
C_conv	17400
da max	71,5 mm
da min	70
Weight	0,218 Kg
LangID	1
ra max.	1 mm
Da max.	85 mm
Oil rpm	8500
da min.	70 mm
r0 max.	0,4 mm
hidYobi	6913N
GRS rpm	7100
hidTable	ecat_NSRDGB
Size (mm)	65x90x13
Prod_Type3	DGBB_SR_N_OT
Width (mm)	13
Bearing number	6913N
Bore Diameter (mm)	65
Outer Diameter (mm)	90
(Oil) Lubrication Speed	8 500 r/min
(Grease) Lubrication Speed	7 100 r/min
Basic dynamic load rating (C)	17,4 kN
Basic static load rating (C0)	16,1 kN