



Bearing No. 6913NR

f	1,12 mm
r	1
d	65 mm
D	90 mm
B	13 mm
C	13 mm
a	2,1 mm
b	1,3 mm
D2	94,4 mm
B_	13
Cy	2.9
ra	1
C0	16.1
fo	16.6
D_	90
D1	87,9 mm
rn	0,5 mm
Z_	19
Dx	96
ro	0.4
DE_	84.644
DA_	7.144
SRI	3.7
D_a	85
SRE	3.7
DI_	70.356
SRIN	-0.02
yobi	6913NR
SBRG	19
bomp	0

SREX	0.02
KBRG	6101
SREN	-0.02
SDM_	77.5
SRIX	0.02
mass	0.218
C_conv	17400
r min.	1 mm
da max	71,5 mm
ALPHA_	0
Weight	0,218 Kg
da min	70
LangID	1
GRS rpm	7100
Da max.	85 mm
hidYobi	6913NR
Oil rpm	8500
da min.	70 mm
r0 max.	0,4 mm
ra max.	1 mm
hidTable	ecat_NSRDGB
Size (mm)	65x90x13
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	13
Bearing number	6913NR
Bore Diameter (mm)	65
Outer Diameter (mm)	90
(Oil) Lubrication Speed	8 500 r/min
(Grease) Lubrication Speed	7 100 r/min
Basic dynamic load rating (C)	17,4 kN
Basic static load rating	16,1 kN

(C0)	
------	--