



Bearing No. 6913ZZ

r	1
d	65 mm
D	90 mm
B	13 mm
C	13 mm
D_	90
C0	16.1
fo	16.6
ra	1
Z_	19
B_	13
DE_	84.644
SRI	3.7
DA_	7.144
DI_	70.356
SRE	3.7
D_a	85
SRIX	0.02
Noun	Bearing
SREX	0.02
SRIN	-0.02
SBRG	19
yobi	6913ZZ
KBRG	6141
Bore	2.559 Inch 65 Millimeter
bomp	0
SDM_	77.5
SREN	-0.02
mass	0.218

UNSPSC	31171504
Weight	0,218 Kg
r min.	1 mm
LangID	1
da min	70
C_conv	17400
ALPHA_	0
da max	71,5 mm
hidYobi	6913ZZ
GRS rpm	7100
Da max.	85 mm
ra max.	1 mm
da min.	70 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	65x90x13
Snap Ring	No
Enclosure	2 Metal Shields
Inventory	0.0
Width (mm)	13
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	2.559
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6913ZZ
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	65MM Bore; 90MM Outside Diameter; 13MM Outer Race Diameter; 2 Metal

	Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.512 Inch 13 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Weight / Kilogram	0.21
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Outer Diameter (mm)	90
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	7 100 r/min
Basic static load rating (C0)	16,1 kN
Basic dynamic load rating (C)	17,4 kN
Maximum Capacity / Filling Slot	No