



Bearing No. 6913ZZ

D	90 mm
C	13 mm
B	13 mm
d	65 mm
rn	0,5 mm
Bore	2.559 Inch 65 Millimeter
Noun	Bearing
r min.	1 mm
da max	71,5 mm
UNSPSC	31171504
Weight	0,206 Kg
da min.	70 mm
Da max.	85 mm
ra max.	1 mm
series:	69
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	65x90x13
Inventory	0.0
Snap Ring	No
Width (mm)	13
bore type:	Round
Weight / LBS	0.451
maximum rpm:	8200 RPM
closure type:	Double Shielded
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Keyword String	Ball

Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6913ZZ
overall width:	13 mm
bore diameter:	65 mm
cage material:	Steel
fillet radius:	1 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Long Description	65MM Bore; 90MM Outside Diameter; 13MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
bearing material:	High Carbon Chrome Steel
outside diameter:	90 mm
inner ring width:	13 mm
Manufacturer Name	NTN
Weight / Kilogram	0.21
outer ring width:	13 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	65
Internal Clearance	C0-Medium

snap ring included:	Without Snap Ring
Outer Diameter (mm)	90
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	16100 N
maximum rpm (grease):	7000 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	17400 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6913ZZ/2AS
Internal Special Features	No
manufacturer product page:	Click here
(Grease) Lubrication Speed	7 000 r/min
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	17,4 kN
Basic static load rating (C0)	16,1 kN
Maximum Capacity / Filling Slot	No