



**Bearing No. 6913ZZ**

D	90 mm
d	65 mm
B	13 mm
C	13 mm
Noun	Bearing
Bore	2.559 Inch   65 Millimeter
Width	13 mm
UNSPSC	31171504
r min.	1 mm
Weight	0.200 Kg
da min.	70 mm
Da max.	85 mm
ra max.	1.0 mm
Category	Single Row Ball Bearing
ra (max)	1 mm
da (min)	70 mm
Da (max)	85 mm
Factor fo	16.5
Inventory	0.0
Bore Size	65 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	65x90x13
Width (mm)	13
Weight / LBS	0.44
Configuration	Single Row
Product Group	B00308
Inch - Metric	Metric

Keyword String	Ball
Bearing number	6913ZZ
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Long Description	65MM Bore; 90MM Outside Diameter; 13MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	<a href="http://www.nachi.com">http://www.nachi.com</a>
Outer Race Width	0.512 Inch   13 Millimeter
Outside Diameter	3.543 Inch   90 Millimeter
Radial Clearance	0.008 to 0.028 mm
Weight / Kilogram	0.2
Manufacturer Name	NACHI
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Static Load Rating	16,000 N
Dynamic Load Rating	17,400 N
Outer Diameter (mm)	90
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	1 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	7,100 rpm
Manufacturer Item Number	6913 ZZ BV2M
Internal Special Features	No
Basic static load rating (C0)	16 kN

Basic dynamic load rating (C)	17,4 kN
Maximum Capacity / Filling Slot	No